



Atlas Audio

4" Shallow Mount Coaxial In-Ceiling Speaker with 16-Watt 70/100V Transformer

FAP42TC

SKU: 25148 UPC: 612079181209

With an overall depth of 4" (102mm) the FAP42TC is the perfect choice when high fidelity audio and wide, even coverage is required but space above the plenum is limited. For wall mount applications (tanning salons or surround sound) the short 4" depth will even work in most stud wall installations. A simplified input section features a 4-pole Phoenix style connector for easy daisy chaining between speakers. A simple cover including combination 1/2" (13mm) / 3/4" (19mm) knock-outs is provided for installation ease. The popular AtlasIED "C-ring / V-Rail" mounting system is provided for quick installation into drop tile acoustic ceilings and existing construction drywall. For new construction drywall applications the optional FAP42-TR may be used. All other popular features of the FAP42T are included on the new FAP42TC including the front mounted tap selector switch (with included transformer bypass for 8 Ohm applications), attractive press-fit grills, high performance 4" polypropylene cone driver with 3/4" (19mm) PEI tweeter and precision crossover components for smooth, even coverage.

Features

- 16-Watt 70/100V Transformer
- "Press Fit" Grilles Blend Better into Contemporary Architecture
- Easy Installation in Drop Tile or Sheetrock Ceilings via C-ring/V-rail Tile Bridge and "Dog Leg" Mounting System (Included)
- Enhanced Quality 70.7V/100V Internal Transformers Minimize Insertion Loss and Maintain Low Frequency Response While Providing increased Output for Higher SPL Applications
- Front Mounted Tap Selector Switch for Easy System Tuning Adjustments Includes Transformer Bypass Setting for 8 ohm Direct Coupled Operation
- Low Depth (4") Speaker System for Limited Space Applications
- UL 1480

Speaker Type	Coaxial
Sensitivity	88dB Average
Power Taps	1, 2, 4, 8, 16 Watts & 8?
Frequency Response	75Hz - 20kHz
Dispersion	130°
Depth	4 1/4" (10.7696 cm)
Diameter	10 1/2" (26.67 cm)
Shipping Weight	13.00 lbs (5.90 kgs)
Safety Listed	1480